

# HEADPHONES HPM1000

## Technical Specifications

Version 1.1 August 2006

ENGLISH



[www.behringer.com](http://www.behringer.com)



# HEADPHONES HPM1000

## MULTI-PURPOSE HEADPHONES

- ▲ Ultra-wide frequency response
- ▲ High dynamic range
- ▲ High-resolution capsule
- ▲ 1/8" connector plus 1/4" adapter included
- ▲ Single-sided cord
- ▲ Oval-shaped ear cups
- ▲ Comfortable headband
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

## SPECIFICATIONS

Frequency response	20 Hz - 20 kHz
Max. power handling	100 mW
Impedance	32 Ohm
Sensitivity	105 dB @ 1 kHz
Cord length	2.0 m
Connector	1/8" TRS connector plus 1/4" TRS adapter

---

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER nor affiliation of the trademark owners with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER International GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903