






### Dimensions






Power Taps (100V).....	10 W / 20W / 40W
Low Impedance position.....	8Ω (160W continuous)
Sensitivity (1W/1m) .....	90 dB
Frequency Response .....	78Hz - 250Hz (+/-3dB)
Dimensions .....	Ø 281 x 110 mm
Mounting Hole .....	Ø 250 mm
Material (front baffle) .....	ABS
Material (grille) .....	Iron
Weight .....	3,1 Kg

Specifications are subject to change without notice



### Dimensiones



<b>Posic. de potencia (100V).....</b>	<b>10 W / 20W / 40W</b>
<b>Posición baja impedancia.....</b>	<b>8Ω (160W continuos)</b>
<b>Sensibilidad(1W/1m) .....</b>	<b>90 dB</b>
<b>Respuesta en frecuencia .....</b>	<b>78Hz - 250Hz (+/- 3dB)</b>
<b>Dimensiones .....</b>	<b>Ø 281 x 110 mm</b>
<b>Dimensiones de montaje .....</b>	<b>Ø 250 mm</b>
<b>Material .....</b>	<b>ABS</b>
<b>Material (rejilla) .....</b>	<b>Hierro</b>
<b>Peso .....</b>	<b>3,1 Kg</b>

Especificaciones sujetas a cambio sin previo aviso