



Metal Housing

4 Microphones

Dual Battery System



The DR-100, designed for professional recording applications in the field, offers high-quality recording directly in WAV or MP3 format from a rugged metal housing. You can choose between two pairs of built-in uni-directional and omni-directional microphones, XLR inputs with switchable 48V phantom power and a mini jack line input. This ensures that virtually all fields of application are covered – from music, speech and atmosphere recordings to meeting minutes and live concert recordings.

Adjust your recording level easily by a twin hardware control rather than a menu option. Start your recordings manually, automatically by level, advanced (by up to 2 seconds), delayed (to prevent key presses from being recorded) or with the help of a remote control. A defeatable loudspeaker for playback is also included. You can make overdubs, manually create a new file during recording, divide a recording and use locate markers. The DR-100 also features switchable automatic analogue gain control with limiter, a low-cut filter with three switchable frequencies, headphones output, an infrared/wired remote control and a USB connector.

- ▶ Handheld digital stereo recorder for professional use
- ▶ Rugged metal chassis
- ▶ MP3 and WAV file recording and playback
- ▶ Records to SD/SDHC card
- ▶ Selectable recording formats:
 - WAV: 16-bit, 24-bit
 - MP3 : 32, 64, 96, 128, 192, 256, 320 KBit/s
- ▶ Sampling rates supported: 96 kHz, 48 kHz, 44.1 kHz
- ▶ Four built-in high-quality condenser microphones
 - Two uni-directional mics for stereo recording
 - Two omni-directional mics for minutes recording
- ▶ Two XLR mic inputs with switchable +48V phantom power
- ▶ High-performance mic preamp provides wide range of gain (–58 dBu to +2 dBu)
- ▶ Use of Audio4pro™ family AD/DA converters by AKM (more than 100 dB SN ratio)
- ▶ Stereo line input with adjustable level to connect an external source (mini jack)
- ▶ Dual hardware controls for intuitive recording level setting
- ▶ Switchable low-cut filter (40 Hz, 80 Hz, 120 Hz)
- ▶ Analogue auto gain control
- ▶ Analogue limiter to prevent clipping (hardware switchable on/off)

- ▶ Built-in monitor speaker (hardware switchable on/off)
- ▶ Headphones output with level control (mini jack)
- ▶ Separate stereo line output (mini jack)
- ▶ Pre-recording buffer (2 seconds) allows a recording to start before the record key is pressed
- ▶ Delayed recording feature to prevent the DR-100 from recording a touch noise of keystroke
- ▶ Auto recording feature (recording is automatically started when the input signal exceeds a threshold level)
- ▶ Overdub feature to add narration, singing or instruments to an existing recording
- ▶ Locate markers
- ▶ File renaming (Date/User Word)
- ▶ File divide function (to cut unwanted noise for instance)
- ▶ Create a new file during recording (manually or automatically by file size)
- ▶ Quick menu allows deleting or tagging a file directly from the home screen
- ▶ Playback features include:
 - In/Out loop
 - Folder or playlist playback
 - MP3 ID3 tag display (up to version 2.4)
 - Pitch control (–50 % to +16 %)
 - Tempo control without affecting the key
- ▶ Camera stand screw hole (¼ inch) on bottom side
- ▶ 2-Gigabyte SD card included
- ▶ USB 2.0 connection for file transfer to/from computer
- ▶ Two options of battery operation with backup function: BP-L2 lithium-ion rechargeable (included) or two easy-to-find AA batteries
- ▶ Wireless remote control, windshield, and softcase included as standard
- ▶ Optionally available:
 - BP-L2 replacement battery
 - PS-P520 AC adapter

DR-100

Portable Stereo Recorder

Specifications

Audio inputs and outputs	
Microphone inputs	XLR-3-32 equivalent (balanced) switchable 48V phantom power
Input impedance	1.2 kOhm
Nominal input level	-58 dBu (GAIN HIGH) -36 dBu (GAIN MID) -14 dBu (GAIN LOW)
Maximum input level	-42 dBu (GAIN HIGH) -20 dBu (GAIN MID) +2 dBu (GAIN LOW)
Line input	3.5 mm stereo minijack
Input impedance	23 kOhm
Input level (nominal/maximum)	-10 dBV/ +6 dBV
Line output	3.5 mm stereo minijack
Output level (nominal/maximum)	-10 dBV/ +6 dBV
Headphones output	3.5 mm stereo minijack
Maximum output power	25 mW + 25 mW (at 32 Ohm)
Built-in loudspeaker	0.4 W output

Audio performance (LINE IN > LINE OUT)	
Frequency response	20 Hz–20 kHz, +1/-3 dB (44.1 kHz) 20 Hz–22 kHz, +1/-3 dB (48 kHz) 20 Hz – 42 kHz, +1/-3 dB (96 kHz, Line input, XLR mic input)
Distortion	Less than 0.01%
S/N ratio	90 dB or more

Audio file compatibility	
MP3 files	Bit rate: 32–320 KBit/s, variable bit rate (playback only), Sampling frequency: 44.1/48 kHz, ID3 tag support up to Version 2.4
WAV files	Sampling frequency: 44.1/48 kHz Bit length: 16/24-bit
Recording medium	SD card (64 MB–2 GB) or SDHC card (4–32 GB)
File system	FAT partition: FAT16/32



Computer requirements	
Supported OS	Windows 2000 Professional SP4 or newer, Windows XP, Windows Vista, Mac OS X 10.2 or newer
Windows	Pentium 300 MHz or better 128 MB or more memory
Macintosh	266 MHz Power PC, iMac, G3, G4 or better 64MB or more memory
USB port	USB 2.0 recommended
USB host controller	Intel chipset recommended

Power supply and other specifications	
Power supply	Lithium-ion battery (BP-L2, included) or NiMH rechargeable batteries (HR15/51) or Alkaline batteries (LR6) or PS-P520 AC adapter (available for purchase)
Battery life (continuous operation, backlight off, MP3 at 128 KBit/s, varies with operating conditions)	Lithium-ion: About 5 hours (recording or playback) NiMH: About 4 hours (recording or playback) Alkaline: About 2 hours (recording or playback)
Operation temperature range	0–40 °C
Power consumption	1.7 W (MP3 playback) 5.5 W (maximum)
External dimensions (W x H x D)	80 mm x 153 mm x 35 mm (excluding protrusions)
Weight	0.29 kg (not including batteries)
Accessories available for purchase	BP-L2 replacement battery PS-P520 AC adapter



Hardware switches rather than menu options allow quick setup of the unit according to the particular recording situation.

© 2009 TEAC Europe GmbH All Rights Reserved. All specifications are subject to change without notice.
All trademarks are property of their respective holders.
Visit www.tascam-europe.com or www.tascam.com for most up-to-date information.

www.tascam-europe.com

TASCAM Division, TEAC Europe GmbH, Bahnstr. 12, 65205 Wiesbaden, Germany

TEAC UK Ltd., Suites 19 & 20, Building 6, Croxley Green Business Park, Hatters Lane, Watford, Hertfordshire, WD18 8TE, UK

TASCAM 
TEAC PROFESSIONAL