

EC105TB/EC105TN

LOUDSPEAKER ENCLOSURE

This compact loudspeaker is equipped with both a 5" driver and tweeter matched with an impedance transformer to the 100V line. Moulded in ABS plastic, it's ideally suited for smaller rooms. A swivel base for ceiling or wall mounting is included. Maximum input power 30/15/7.5/5 W, Sensibility 90dB/1W/1m, Frequency range 80 - 20.000 Hz. Weight 2,3 Kg. Size in mm 155 x 260 x 162.

Available in white or black.

CAJA ACÚSTICA

Caja acústica de pequeñas dimensiones equipada con un altavoz de 5" y tweeter con transformador de impedancias para línea de 100V. Fabricada en plástico ABS, ideal para sonorización de pequeñas salas. Incluido anclaje para su instalación en pared o techo, totalmente orientable. Potencias admisibles 30/15/7,5 y 5 W, rendimiento 90dB/1W/1m, respuesta en frecuencia 80-20.000 Hz. Peso 2,3 Kg. Dimensiones en mm 155 x 260 x 162. Disponible en blanco y negro.



EC105T

technical characteristics

	EC105T
Ways	2
Nominal impedance	8Ω
Max. RMS power	50 W
Program power	100 W
Transformer power tapings	30/15/7,5/5 W
Transformer impedance	0,3 / 0,6 / 1,3 / 2 kΩ
Frequency response	80Hz-20KHz
Max SPL at 1m	105 dB
Efficiency 1W/1m	90 dB
Dimensions wxhxd	155x260x162 mm
Weight	2,3 kg